



# INKJET MACHINES

## Latest Models AP200

### AP200 Pouch Label Applicator

Easily and consistently apply labels to pouches

### AP200

POUCH STYLE  
LABEL APPLICATOR

The AP200 is a semi-automatic labeling machine designed for applying labels to unfilled pouches. Labels are easily applied as each pouch is dropped into the machine.

Intuitive setup and operation allows for consistent placement and even application. The ultrasonic media sensor is easily trained to detect gaps in a wider range of media than mechanical flag sensors common in other applicators, allowing the AP200 to perform consistently—even on thin, clear, or reflective materials.

#### Key Features

- ✓ Designed for unfilled pouches
- ✓ Consistent and accurate label placement
- ✓ Apply one or two label sizes per container



#### Adjustable Guides

Easily accommodates pouch widths from 3.2" (80mm) to 9.8" (250mm)

#### Ultrasonic sensor

Reliably sense gaps in a wide range of media

#### LCD Display & Counter

View and program settings.  
Track the number of labels applied

#### Easy Operation

Simply drop each pouch between the guides to apply labels



T:0161 343 1131 [www.magnum-uk.com](http://www.magnum-uk.com)



FOR ALL YOUR PRINTING NEEDS



# INKJET MATERIAL

## Latest Products AP200

### AP200 Pouch Label Applicator



#### Stop applying labels by hand

Gain efficiency and consistency when applying labels to your pouches. The AP200 allows for a faster and easier workflow, while ensuring your labels are straight and evenly placed—giving your final products a professional look.

### AP200 Specifications

<b>Supply voltage</b>	North America - 110V AC, 60 Hz Europe, Middle East, Asia - 220V AC, 50Hz	<b>Width of label</b>	1" (25mm) to 9.00" (230mm)
<b>Power consumption</b>	< 100VA.	<b>Length of Label</b>	1" (25mm) to 11.81" (300mm)
<b>Dimensions</b>	17.3" (440mm) W, 9" (230mm) H, 13" (330mm) D	<b>Label gap</b>	> 0.1 inches (2.5mm)
<b>Machine weight</b>	33 lbs (15kgs)	<b>Diameter of label roll</b>	< 7.87 inches (200mm)
<b>Width of pouch</b>	3.2" (80mm) to 9.8" (250mm)	<b>Core diameter</b>	2 to 3 inches (50 to 76mm)
<b>Length of pouch</b>	4.75" (120mm) to 13.75" (350mm)	<b>Label feed speed</b>	0.03 to 0.1m/sec - programmable
<b>Thickness of pouch</b>	< 0.2" (5mm)	<b>Min. distance from pouch leading edge to label start</b>	> 1.57" (40mm)
<b>Label modes</b>	1 or 2 labels per pouch		

## AP200

### POUCH STYLE LABEL APPLICATOR

